

# MATERIAL SAFETY DATA SHEET

## SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION

**PRODUCT NAME:** **Simplicite' Puramist**

Part Number:

GENERAL USE: Cleaning solvent

PRODUCT DESCRIPTION: Clear flammable liquid, characteristic odor



MANUFACTURER'S NAME

Nail Systems International

DATE PREPARED: January 31, 2003

SUPERSEDES: October 15, 2001

Page 1 of 4

ADDRESS (NUMBER, STREET, P.O. BOX)

2 Union Hill Road

TELEPHONE NUMBER FOR INFORMATION

(610) 825-1524

(CITY, STATE AND ZIP CODE)

W. Conshohocken, PA 19428

COUNTRY

USA

EMERGENCY TELEPHONE NUMBER

Infotrac (800) 535-5053 Outside USA (352) 323-3500

DISTRIBUTOR'S NAME

Same

ADDRESS (NUMBER, STREET, P.O. BOX)

TELEPHONE NUMBER FOR INFORMATION

(CITY, STATE AND ZIP CODE)

COUNTRY

EMERGENCY TELEPHONE NUMBER

## SECTION 2 - HAZARDOUS INGREDIENTS

HAZARDOUS COMPONENTS	% (by weight)	CAS #	EINECS #	Hazard Symbol	RISK PHRASES Full Text Section 16
Isopropyl alcohol	98	67-63-0	200-661-7	F, Xi	R-11, 36, 67

## SECTION 3 - HAZARDS IDENTIFICATION

### EMERGENCY OVERVIEW

Flammable liquid, irritating to eyes, skin and respiratory system. Hazard symbols for this product: F, Xi Risk Phrases: 11, 36, 66, 67

### POTENTIAL HEALTH EFFECTS

INHALATION: High concentrations are irritating to the respiratory tract; may cause headache, dizziness, nausea, vomiting and malaise.

SKIN: Brief contact may cause slight irritation; prolonged contact may cause moderate reddening, swelling and possible necrosis.

EYES: Contact causes severe irritation and pain associated with redness and swelling of the conjunctiva.

INGESTION: Moderately toxic; may cause headache, dizziness, diarrhea and general weakness; large doses may result in red blood cell hemolysis.

CARCINOGENICITY

NTP? No IARC MONOGRAPHS? No OSHA REGULATED? No

**MATERIAL SAFETY DATA SHEET**

PRODUCT NAME: Simplicite' Puramist  
January 31, 2003

**SECTION 4 - FIRST AID MEASURES**

**INHALATION:** Remove affected person to fresh air; provide oxygen if breathing is difficult; if affected person is not breathing, administer CPR and seek emergency medical attention.

**SKIN:** Remove contaminated clothing; wash affected area with soap and water; launder contaminated clothing before reuse; if irritation persists, seek medical attention.

**EYES:** Remove contact lenses. Flush eyes with clear running water for 15 minutes while holding eyelids open; if irritation persists, seek medical attention.

**INGESTION:** Give two glasses of water for dilution; Induce vomiting by sticking fingers down throat; never give anything by mouth to an unconscious person; seek medical attention.

**SECTION 5 - FIRE FIGHTING MEASURES**

**GENERAL HAZARDS:** Product is flammable. Products of combustion include compounds of carbon, hydrogen and oxygen, including carbon monoxide. Vapors may cause a flash fire or ignite explosively. Vapors may travel a considerable distance to a source of ignition and flash back.

**EXTINGUISHING MEDIA**  
Carbon dioxide, water fog, dry chemical, chemical foam

**FIRE FIGHTING PROCEDURES**  
Firefighters must wear full facepiece self - contained breathing apparatus in positive pressure mode. Do not use solid stream of water since stream will scatter and spread fire. Fine water spray can be used to keep fire - exposed containers cool.

**UNUSUAL FIRE AND EXPLOSION HAZARDS**  
Closed containers can explode due to buildup of pressure when exposed to extreme heat. Do not use direct stream of water on pool fires as product may reignite on water surface. Caution - Material is flammable!

**HAZARDOUS COMBUSTION PRODUCTS**  
Smoke, fumes, oxides of carbon

**SECTION 6 - ACCIDENTAL RELEASE MEASURES**

**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:** CAUTION - FLAMMABLE - Evacuate and ventilate area; confine and absorb into absorbent; place material into approved containers for disposal. Do not discharge into lakes, ponds, streams or public waters.

**SECTION 7 - HANDLING AND STORAGE**

**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:** Keep container closed when not in use; protect containers from abuse; protect from extreme temperatures. CAUTION - FLAMMABLE - keep away from all sources of ignition. "Empty" containers may contain residue which may form explosive vapors. Do not weld or cut near empty container that has not been professionally reconditioned. Use non-sparking tools when opening and closing containers. Maintain well ventilated work areas to minimize exposure when handling this material.

**SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION**

HAZARDOUS COMPONENTS	NIOSH				ACGIH			
	TWA ppm	TWA mg/m3	STEL ppm	STEL mg/m3	TWA ppm	TWA mg/m3	STEL ppm	STEL mg/m3
Isopropyl alcohol	400	980	500	1225	400	983	500	1230

**PERSONAL PROTECTION:**  
**RESPIRATORY PROTECTION (SPECIFY TYPE):** None required while threshold limits (Section 2) are kept below maximum allowable concentrations; if TWA exceeds limits, NIOSH approved respirator must be worn. Refer to 29 CFR 1910.134 or European Standard EN 149 for complete regulations.

**PROTECTIVE GLOVES:** Neoprene or rubber gloves with cuffs.

**EYE PROTECTION:** Protective eyeglasses or chemical safety goggles. Refer to 29 CFR 1910.133 or European Standard EN166.

**OTHER PROTECTIVE CLOTHING OR EQUIPMENT:** Safety eyebath nearby

**WORK / HYGIENIC PRACTICES:** Practice safe workplace habits. Minimize body contact with this, as well as all chemicals in general.

**MATERIAL SAFETY DATA SHEET**

PRODUCT NAME: Simplicite' Puramist  
January 31, 2003

Page 3 of 4

**SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES**

APPEARANCE AND ODOR Clear liquid, characteristic odor	VAPOR PRESSURE 31 mm Hg @ 20° C
pH Not applicable	SPECIFIC GRAVITY (WATER = 1) 0.787
BOILING POINT / BOILING RANGE 180° F (82° C)	SOLUBILITY IN WATER Complete
FLASH POINT 53° F (11.7° C) TCC	VISCOSITY Not specified
FLAMMABLE LIMITS LEL: 2.0% UEL: 12.7%	VAPOR DENSITY (AIR = 1) > 1
AUTOIGNITION TEMPERATURE 750° F (399° C)	EVAPORATION RATE (WATER = 1) < 1

**SECTION 10 - STABILITY AND REACTIVITY**

STABILITY UNSTABLE: STABLE: XXX	CONDITIONS TO AVOID: Extreme temperatures, open flames, sparks
---------------------------------------	----------------------------------------------------------------

INCOMPATIBILITY (MATERIALS TO AVOID): Strong oxidizers, strong acids

HAZARDOUS DECOMPOSITION OR BYPRODUCTS: Decomposition will not occur if handled and stored properly. In case of a fire, oxides of carbon, hydrocarbons, fumes, and smoke may be produced.

HAZARDOUS POLYMERIZATION MAY OCCUR: WILL NOT OCCUR: XXX	CONDITIONS TO AVOID: None
---------------------------------------------------------------	---------------------------

**SECTION 11 - TOXICOLOGICAL INFORMATION**

Hazardous Components	CAS # EINECS #	LD50 of Ingredient (Specify Species and Route)	LC50 of Ingredient (Specify Species)
Isopropyl alcohol	67-63-0 200-661-7	5840 mg / kg Oral - rat	22,500 ppm / 4H Inhalation - rat

**SECTION 12 - ECOLOGICAL INFORMATION**

No data are available on the adverse effects of this material on the environment. Neither COD nor BOD data are available. Based on the chemical composition of this product it is assumed that the mixture can be treated in an acclimatized biological waste treatment plant system in limited quantities. However, such treatment should be evaluated and approved for each specific biological system. None of the ingredients in this mixture are classified as a Marine Pollutant.

**SECTION 13 - DISPOSAL CONSIDERATIONS**

WASTE DISPOSAL METHOD: Dispose of in accordance with Local, State, and Federal Regulations. This product may produce hazardous vapors or fumes in a closed disposal container creating a dangerous environment. (USA) Refer to "40 CFR Protection of Environment Parts 260 - 299" for complete waste disposal regulations. Consult your local, state, or Federal Environmental Protection Agency before disposing of any chemicals. Do not flush to sanitary sewer or waterway.

**SECTION 14 - TRANSPORT INFORMATION**

PROPER SHIPPING NAME: Isopropyl alcohol mixture

DOT HAZARD CLASS / Pack Group: 3 / II  
REFERENCE: 49 CFR 173.150, .202, .242  
UN / NA IDENTIFICATION NUMBER: UN 1219  
LABEL: FLAMMABLE LIQUID  
HAZARD SYMBOLS: F

IATA HAZARD CLASS / Pack Group: 3 / II  
IMDG HAZARD CLASS: 3  
RID/ADR Dangerous Goods Code: 3 (3B)  
UN TDG Class / Pack Group: 3 / II

Note: Transportation information provided is for reference only. Client is urged to consult CFR 49 parts 100 - 177, IMDG, IATA, EU, United Nations TDG, and WHMIS (Canada) TDG information manuals for detailed regulations and exceptions covering specific container sizes, packaging materials and methods of shipping.

